

focus on **Laboratory Products**

An Easy to Use Tool for Safe and Reproducible High Pressure Reaction Chemistry

Tom McNally, Martyn Fordham

For the efficient synthesis of novel molecules, materials and polymers scientists employ a broad range of experimental techniques and equipment. Reactions carried out at very low temperature under an inert atmosphere at high dilution can usually be performed in a conventional round bottom flask whereas reactions that require elevated temperature and high pressure need to be carried out in a specially designed high pressure reactor.

A high pressure reactor can offer several advantages over a conventional round bottom flask for conducting chemical reactions. It enables reactions to be carried out under elevated pressure and at temperatures higher than the boiling point of the reaction solvent or solvent mixture. These factors can lead to a significant increase in reaction rate to produce the desired product and thereby minimise the decomposition of substrates and/or products leading to a cleaner reaction profile. It may seem counterintuitive, but carrying out a reaction under pressure in a suitably designed reactor, can lead to an increase in the safety of a procedure by containing potentially toxic materials or gases in a controlled environment. However not all commercial high pressure reactors are the same, they differ considerably in their quality of construction, safety features, ease of set-up and use, ease of maintenance and versatility to handle different corrosive materials and reactants under high pressure.



In the School of Chemistry at the University of Nottingham (UK), high quality cutting edge collaborative research is carried out in many areas including nanotechnology, synthetic methodology, natural product synthesis, materials chemistry and the utilisation of supercritical fluids as alternative solvents for synthesis. One area of specialism is the use of supercritical fluids, such as carbon dioxide, as a “green” solvent for polymer synthesis and materials processing. This research is led by Professor Steven Howdle and his group required access to equipment which would enable the development of efficient synthetic protocols for the preparation and isolation of a variety of polymeric materials quickly, easily and most importantly, given that the reactions would be carried out at elevated temperatures and high pressures, in a safe manner. The group investigated a number of high pressure reactors which were commercially available at the time however they did not meet the groups’ requirements in terms of ease of set-up, operation, cleaning, versatility of use and safety.

Driven by their desire for an affordable high pressure reactor that combined ease-of-use, outstanding performance, ease of maintenance and high operational safety, Professor Howdle embarked on a project with colleagues Martin Dellar, Peter Fields and Richard Wilson based in the University’s workshops, to design and develop a bespoke high pressure reactor.

Design for a New High Pressure Reactor

A major design feature introduced into the new reactor was a novel clamp. This is used to fasten the body of the reactor to the head piece which contains valves to allow the introduction of reagents and gases as well as monitoring the pressure and temperature of the reaction. A clamp design to secure the body to the head was favoured rather than use of a screw thread, as in the latter, there is the possibility of cross threading and accumulation of materials in the screw path required to join the sections together.

As stated above, safety in use was a key design feature required by the scientists who would use the equipment. One potential safety issue which had been identified in a clamp design was the possibility of opening the reactor whilst still under pressure when undoing the clamp. When a regular high pressure valve is opened at the end of the reaction, it could be assumed that the pressure has been released. However it is possible to have a small blockage in a valve leading to some residual pressure. If the clamp was removed under such conditions, the head metal could have sufficient momentum to fly off and potentially cause serious injury to the scientist. This required a safety design feature to be developed for the new reactor to ensure that all residual pressure was always released

Nottingham engineers came up with a novel safety valve design. At the end of the reaction, after the pressure had been released and the pressure gauge read zero, a valve could be removed to leave behind a hole of a few millimetres in diameter ensuring any residual pressure would be released. A further safety feature was that the head of the safety valve also operated as the key which had to be physically inserted into the clamp to undo and remove it. Therefore it would not be possible to manipulate the clamp in any way without firstly removing the safety key and hence releasing any unexpected residual pressure in the reactor.

This simple yet highly effective safety feature, inherent in the design of the new reactor is shown in *Figure 1*.



Figure 1. PressureSyn safety key

Each key in the new design is individually engineered to fit only one clamp therefore it is not possible to undo the clamp using another key whilst there is the possibility of the reactor being under pressure. In order to ensure that the clamp did not introduce areas of stress into the body of the reactor, measurements were made of the complete assembly. As shown in *Figure 2* there are no significant stress seen in the area where the clamp is fixed onto the reactor body.




Figure 2. Stress measurement patterns on PressureSyn reactor body

To ensure the operational integrity of the new design, the PressureSyn reactors have been extensively tested and used by various research groups in the School of Chemistry at the University of Nottingham. Using a wide range of standard operating procedures developed for specific experimental conditions there have been no safety incidents reported, which proves testament to the safety key design. A variety of reactions carried out in the PressureSyn reactor have been reported in the literature [1, 2]. In a recent publication by Howdle et al (J. Am. Chem. Soc. 2012, 134, 4772-4781) work towards the synthesis of structured block copolymers which are important in myriad applications from catalyst supports to data storage was reported. The known synthetic routes to these important materials had limitations which hindered industrial scale manufacture. Using the PressureSyn reactor, Professor Howdle developed a new reliable and controllable route via reversible addition-fragmentation chain transfer (RAFT) dispersion polymerisation in supercritical CO₂ to give access to these materials in a versatile one-pot process.

Additional Reactions Carried out in the PressureSyn Reactor

The flexibility of the design enables the PressureSyn reactor be utilised in a wide range of high pressure reactions. The reactor head is fitted with a number of ports including pressure gauge, pressure relief valve/bursting disk safety features, outlet valve, thermocouple, gas inlet valve and safety valve. As an alternative configuration, replacement of the gas inlet valve with a blanking valve would allow the PressureSyn to be utilised as a standard autoclave. PressureSyn reactors are produced as standard in durable SS316 stainless steel however the same design can be used to manufacture units in acid resistant alloys such as Hasteloy.

If required, the reactor can be fitted with a magnetic stirrer bar and used in collaboration with a metal heating jacket and placed on a stirrer hotplate as shown in *Figure 3*. The specification of the reactor enables reactions to be performed up to maximum working pressure of 100bar @200°C.



Figure 3. PressureSyn Reactor on stirrer hotplate

A further situation for which the PressureSyn reactor is eminently suited is in homogeneous or heterogeneous reactions which require a gas at higher than atmospheric pressure. A common reaction in organic synthesis is the hydrogenation of various functional groups, using gaseous hydrogen at a variety of pressures, to synthesise novel molecules or remove protecting groups required in synthetic routes e.g. in natural product synthesis or potential drug molecules. Examples of reactions which have been safely carried out include the hydrogenation of aromatic and heteroaromatic rings and reduction of nitro groups to amines using metal catalysis. These reactions are commonly utilised in a number of processes in various industries including the pharmaceutical arena where the scale of such reactions may be a few mg to kilograms and above. Whilst a manufacturing process for the synthesis of an active pharmaceutical ingredient (API) is being developed, it can be a distinct advantage to process chemists to be able to carry out reactions at various scales utilising comparable conditions to those used in the discovery phase. This is eminently possible by using the same design of reactor manufactured on a larger scale. Potentially toxic gases e.g. CO can be used to safely carry out synthetic manipulations an area which is becoming commonly used in organic synthesis in both industry and academia.

There have also been requests to use the PressureSyn reactor in the healthcare, oil and food industries where scientists have to routinely carry out reactions requiring high temperature and pressure.

Potential Future Enhancements to the Reactor Design.

When scientists perform a pressure reaction in the laboratory, in addition to careful monitoring of pressure and temperature, an understanding of the reaction profile is often required. Therefore future developments for the PressureSyn reactor under investigation include options where viewing ports could be incorporated or infrared, Raman or UV visible spectroscopic probes could be attached. It would also prove beneficial to have the facility to remove samples to monitor the progress of a reaction or to inject further reagents which may be possible whilst under pressure utilising an HPLC pump. These opportunities come from the flexibility of the design of the apparatus and will help scientists to pursue their research in the most efficient manner possible.

Conclusions

The PressureSyn reactor, with the incorporation of a unique safety key concept developed by scientists and engineers at the University of Nottingham, has enabled a variety of novel research approaches at elevated temperatures and high pressures to be undertaken in a safe and efficient manner. The outcomes of this work have led Professor Howdle and colleagues to produce significant improvements in applied materials research, production of commercially important polymeric materials and have impacted significantly in the area of healthcare. As a result of many years close collaboration with Asynt Ltd, on a series of laboratory reactor and heating system development projects, the company was chosen by the University to commercialise the PressureSyn reactor.

For further information please visit:
<http://www.asynt.com/product/pressuresyn/>

References

1. Busby, A. J.; Zhang, J.; Naylor, A.; Roberts, C. J.; Davies, M. C.; Tendler, S. J. B.; Howdle, S. M. J. *Mater. Chem.* 2003, 13 (11), 2838-2844
2. Maria del Carmen Gimenez-Lopez, Alessandro La Torre, Michael W. Fay, Paul D. Brown, and Andrei N. Khlobystov, *Angew. Chem. Int. Ed.* 2013, 52, 2051-2054

The Authors

Tom McNally is currently a Business Science Fellow in the Business Partnership Unit within the School of Chemistry at the University of Nottingham (UK). He was previously a team leader in the Medicinal Chemistry department of AstraZeneca working on projects to discover novel treatments for respiratory and allergic diseases.

Martyn Fordham is founder and Managing Director of Asynt Ltd and may be contacted for further information on the new PressureSyn high pressure reactor on martyn.fordham@asynt.com



Read, Share and Comment on this Article, visit: www.labmate-online.com/articles

New QR Code Scanning Provides all Product Information with One Click



Glassco are pleased to introduce to you the concept of QR CODE scanning. All you need to do is just put your mobile phone which has a QR reader application against the QR code that is given on the box and all the information with regard to the certificate of conformity and the certificate of calibration (in case of volumetric glassware) can be taken out with a single click.

All the product information is now available at your fingertips. This includes the product specification, the standard used for making the product, the raw material used for making the product and all the necessary calibration information with tolerances that is on the calibration certificate.

Glassco launched 3 new models of hot plate stirrers and many new instrument launches are in the pipeline within this year. To assist in their expansion Glassco would also welcome dealer enquiries.

For More Info, email: 29515pr@reply-direct.com